

RPL#5 Rust Preventative

Features & Benefits

- Long-Term Indoor Humidity Protection
- Salt Spray Protection
- Water Displacing
- Ease of Removal
- Oily Lubricating Film
- Protects Ferrous & Non-Ferrous Metals

PRODUCT DESCRIPTION

RPL #5 is a water displacing, non-staining rust preventive and lubricant that provides an oily protective film for 18 to 24 months indoor storage protection, moderate salt spray protection and short term outdoor protection.

The RPL #5 can be applied by spraying, brushing, dipping or submersion. The thin oily film suppresses fingerprints and is easily removed by wiping or cleaning with solvent or alkaline cleaners.

PROTECTION

Indoors 18 to 24 months
 Outdoors short term

TYPICAL ANALYSIS

APPEARANCE:..... Amber Fluid
 DENSITY: 7.01 LB/GL
 SPECIFIC GRAVITY:.....0.84 @ 60° C
 VISCOSITY:.....42 SUS @ 100° F
 FLASH POINT: > 240°F (COC)
 FILM TYPE: Soft, Oily

PACKAGING

L-2515-14 1 Gallon (4/case)
 L-2515-05 5 Gallon
 L-2515-55 55 Gallon



7403 Wright Rd. Houston, TX 77041
 ph: 832.399.1000 fax: 832.399.1010
 www.ashburnchemical.com