

Clear Coat 33

PRODUCT DESCRIPTION

CLEAR COAT 33 is water-soluble rust and corrosion preventative designed for protection of ferrous and nonferrous materials. This product will provide up to 6 months of rust protection. Leaves a solid, clear, non-tacky coating. Does not leave fingerprints.

APPLICATION

CLEAR COAT 33 should be used straight (undiluted)
Can be applied by brushing, dipping, spraying, or flooding.

NOTE: Dry times for coating will vary with conditions.

Normal Dry Time 20 minutes min.

Heat 100 - 110° F 15 minutes min.

High Humidity..... 40 minutes min.

For best results, allow 60 minutes drying time.

Once the film is hard, part can be handled.

Dust and dirt can be wiped off without affecting film.

Fingerprint free once dried.

TYPICAL ANALYSIS

APPEARANCE:..... Tan Opaque Liquid
ODOR:..... Mild, Waxy Odor
SPECIFIC GRAVITY:.....1.0
pH:.....8.0
RESIDUE:.....Solid Clear Coating

PACKAGING

L-3300-14 1 Gallon (4/case)
L-3300-05 55 Gal Pail
L-3300-55 55 Gal Drum
L-3300-275 275 Gal Tote



7403 Wright Rd. Houston, TX 77041
ph: 832.399.1000 fax: 832.399.1010
www.ashburnchemical.com