



VANISHING OIL QD

FEATURES & BENEFITS

- No residue
- Non-reactive to metals
- Ideal for drawing and stamping (light gauge material)
- Works on ferrous and nonferrous metals
- Excellent lubrication

PRODUCT DESCRIPTION

ASHBURN VANISHING OIL QD is a very low viscosity oil which is fortified with mild extreme pressure additives. It will evaporate completely with no residue.

This product leaves an excellent finish on cut, drawn or stamped part

APPLICATION

ASHBURN VANISHING OIL QD is ready to use, do not dilute.

TYPICAL ANALYSIS

APPEARANCE: Clear Oil
 DENSITY: 6.3 LB/GL
 FLASH POINT: 129°F (ASTM D3278 Closed Cup)
 VISCOSITY: 2.2 - 3.1 cSt @ 40°C
 SULFUR: NONE
 CHLORINE: NONE
 PHOSPHOROUS: NONE

NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metalworking fluid additives.

PACKAGING

E-7530-14	1 Gallon (4/case)
E-7530-05	5 Gallon
E-7530-55	55 Gallon
E-7530-275	275 Gallon