



# CUTTING OIL SLV

## FEATURES & BENEFITS

- Light viscosity
- Excellent chip removal
- Improved finish
- Excellent lubricity
- Residue resists rust and corrosion
- Biodegradable

## PRODUCT DESCRIPTION

**CUTTING OIL SLV** is a synthetic, light viscosity cutting and grinding oil. Its unique fatty acid composition provides natural and extended product stability. Excellent for use in grinding, machining and sawing. It is a biodegradable product that does not contain petroleum oil, chlorine or sulphur. It is ideal for both ferrous and nonferrous materials.

## APPLICATION

Use full strength. Do not dilute. Can be used with all micro-lubricant applicators.

## TYPICAL ANALYSIS

APPEARANCE:..... Light Oil, Light Viscosity, Fatty Odor  
 SULFUR CONTENT: .....None  
 TOTAL CHLORINE: .....None  
 WEIGHT: ..... 7.6 LB/GL  
 FLASH POINT:..... >450°F (TCC METHOD)  
 SMOKE POINT:.....417°F (214 C)  
 VISCOSITY: ..... 195 SUS @ 100°F  
 FATTY OILS: ..... >10%  
 POUR POINT: ..... 0°F

## NOTES

- Use Ashburn Machine Cleaner for quick and thorough pre-cleaning of machine tools and coolant systems.
- Consult Ashburn prior to use on metals or applications not recommended.
- Unless recommended by Ashburn, this product should not be mixed with metalworking fluid additives.

## PACKAGING

E-1100-14	1 Gallon (4/Case)
E-1100-05	5 Gallon
E-1100-55	55 Gallon
E-1100-275	275 Gallon