ASHBURN 2900 RI



FEATURES & BENEFITS

- Water soluble
- Multi-purpose
- · Excellent rust prevention
- Soft residue

RUST INHIBITOR

PRODUCT DESCRIPTION

ASHBURN 2900 RI is a multi-purpose, synthetic, water-soluble rust and corrosion preventative designed for in-process protection of ferrous materials. This product will provide up to 9 months of indoor rust protection. Parts protected with 2900 RI can be welded or painted over.

Ashburn 2900 RI can also be used as a parts cleaner to remove dirt, grime and oil from metal surfaces while providing corrosion protection.

TYPICAL ANALYSIS

APPEARANCE:	Clear Amber Fluid
pH @ 5% CONC:	9.0
SPECIFIC GRAVITY:	1.016
FLASH POINT:	Not Flammable
RESIDUE:	Soft Film
WEIGHT:	8.48 LB/GL

APPLICATION

The 2900 RI can be applied by dipping, spraying, or flooding. Dilute the product 10:1 with water for heavy-duty applications, 15:1 - 25:1 for moderate applications, and 30:1 - 50:1 for light duty applications.

REFRACTOMETER READINGS

Dilution Ratio	12.0%	10.0%	7.0%	5.0%
Refractometer Reading	2.5	2.0	1.4	1.0

PACKAGING

B-2905-05 5 Gallon (4/Case) B-2905-55 55 Gal Pail B-2905-275 275 Gal Drum











